



KEEP OUT OF REACH OF CHILDREN. DO NOT INGEST. AVOID SKIN CONTACT.
If ingested, medical attention may be needed. Store out of direct sunlight between 64° - 77°F (18° - 25°C).

Comparison of the different DTGPRO / DTFPRO solutions
Cleaning | Xtreme Cleaning | Capping | Maintenance | De-Plasticizing

CLEANING SOLUTION: For flushing of printheads. This solution is for use in resolving minor clogs. Flush your print-heads with this solution (if your system is damper/CIS based), or fill it into "cleaning cartridges" and run up to 3 cleaning cycles with those cartridges (if your system is cartridge based). Do not use for wet capping.

CLEANING SOLUTION

For flushing of printheads

This solution is for use in resolving minor clogs. Flush your print-heads with this solution (if your system is damper/CIS based), or fill it into "cleaning cartridges" and run up to 3 cleaning cycles with those cartridges (if your system is cartridge based). Do not use for wet capping.

XTREME CLEANING SOLUTION: For flushing of ink tubing, or to unplug stubborn clogs in printheads. This solution is for use in resolving stubborn/extreme clogs, or to flush out inks from ink tubing (such as if you want to change out inks). Flush your print-heads with this solution (if your system is damper/CIS based) or fill it into "cleaning cartridges" and run up to 3 cleaning cycles with those cartridges (if your system is cartridge based). Do not use for wet capping.

XTREME CLEANING SOLUTION

For flushing of ink tubing, or to unplug stubborn clogs in printheads

This solution is for use in resolving stubborn/extreme clogs, or to flush out inks from ink tubing (such as if you want to change out inks). Flush your print-heads with this solution (if your system is damper/CIS based), or fill it into "cleaning cartridges" and run up to 3 cleaning cycles with those cartridges (if your system is cartridge based). Do not use for wet capping.

CAPPING SOLUTION: For printhead wet capping. This solution is for wet capping & short-term maintenance - to be used for saturating the printhead resting cap on the capping station at the end of the day, and not intended to be used as a cleaning or unclogging solution (use the Cleaning Solution or Xtreme Cleaning Solution for resolving clogs/cleaning purposes). For long-term maintenance (such as when you're going on vacation), use the Maintenance Solution instead.

CAPPING SOLUTION

For printhead wet capping

This solution is for wet capping & short-term maintenance - to be used for saturating the printhead resting cap on the capping station at the end of the day, and not intended to be used as a cleaning or unclogging solution (use the Cleaning Solution or Xtreme Cleaning Solution for resolving clogs/cleaning purposes). For long-term maintenance (such as when you're going on vacation), use the Maintenance Solution instead.

MAINTENANCE SOLUTION: For printhead maintenance (Vacation Mode). This solution is to keep your printheads lubricated and to preserve them in the condition they currently are in. Before using this solution you should ensure that your printheads are working properly with no clogs or gaps on nozzle tests. NOTE: This maintenance solution does NOT clean or unclog your printhead (use the Cleaning Solution or Xtreme Cleaning Solution for those purposes).

MAINTENANCE SOLUTION

For printhead maintenance (Vacation Mode)

This solution is to keep your printheads lubricated and to preserve them in the condition they currently are in. Before using this solution you should ensure that your printheads are working properly with no clogs or gaps on nozzle tests. NOTE: This maintenance solution does NOT clean or unclog your printhead (use the *Cleaning Solution* or *Xtreme Cleaning Solution* for those purposes).

DE-PLASTICIZING SOLUTION: Apply with cleaning swabs to ink that has solidified around your printhead, capping station, or on the wiper blade. DO NOT insert this solution into the capping station or into your printhead channels.

DE-PLASTICIZING SOLUTION

For removing hardened or plasticized ink from around the printhead or capping station

Apply with cleaning swabs to ink that has solidified around your printhead, capping station, or on the wiper blade. DO NOT insert this solution into the capping station or into your printhead channels.